

TALOS		240	230	220	210	130	120
Engine		FPT	FPT	FPT	FPT	LS	LS
Number of cylinders/intake		4/TI	4/TI	4/T	4/T	4/T	4
Cubic capacity	cm ³	4500	3200	3200	3200	2505	2505
Nominal engine speed	rpm	2300	2300	2300	2300	2600	2600
Output at nominal engine speed (ECE R 120) ¹	kW/hp	70/95	65/87	57/78	52/71	41/55	35/47
Max. output (in accordance with ECE R 120) ¹	kW/hp	71/97	65/88	59/80	53/72	41/55	35/47
Transmission type		Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Ratios (F/R)		20/20	20/20	20/20	20/20	16/16	16/16
Min. speed	km/h	0.2	0.19	0.19	0.19	1.21	1.21
Top speed	km/h	40	40	40	40	30	30
PTO speed		540/540 ECO/1000	540/540 ECO/1000	540/540 ECO/1000	540/540 ECO/1000	540/540 ECO/1000	540/540 ECO/1000
Clutch actuation		Electrohydraulic	Electrohydraulic	Electrohydraulic	Electrohydraulic	Electrohydraulic	Electrohydraulic
Max. flow at rated speed	l/min	60	60	60	60	36	36
Number of spool valves (number of connections)		3 (6)	3 (6)	3 (6)	3 (6)	2 (4)	2 (4)
Max. lifting capacity at rear linkage	kg	3100	3100	3100	3100	2200	2200
Overall length	mm	3997	3997	3997	3997	3576	3552
Height with cab	mm	2719	2702	2668	2668	2506	2506
Wheelbase	mm	2287	2200	2200	2200	2046	1937
Turning radius	m	3.5	3.4	3.4	3.4	3.7	3.4
Tare weight with cab	kg	3267	3103	3066	3066	2260	2240

1 Meets ISO TR 14396

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.